Innovation for a Better Life





# CHANGE YOUR ENERGY CHARGE YOUR LIFE



R SU



## Compact Size & Easy Installation

The compact and lightweight nature of the RESU is world-class. It is designed to allow easy wall-mounted or floor-standing installation for both indoor and outdoor applications. The inverter connections have also been simplified, reducing installation time and costs.



#### **Powerful Performance**

The new RESU series features industry-leading continuous power (4.2kW for RESU6.5) and DC round-trip efficiency (95%, 0.3C). LG Chem's L&S (Lamination & Stacking) technology provides durability with long lifespan.



# **Proven Safety**

LG Chem places the highest priority on safety and utilizes the same technology for its ESS products that has a proven safety record in its automotive battery. All products are fully certified in relevant global standards.

\* The ees award is one of the most honorable awards presented annually at ees Europe, the largest exhibition for batteries and energy storage systems in Europe, with the purpose to pay tribute to pioneering products and solutions for energy storage system.

www.lgesspartner.com





## Change Your Energy, Charge Your Life







Models	RESU7H RESU10H		J10H
	Type-R	Type-R	Type-C
gy [kWh]	7.0	9.8	9.8
ergy [kWh]	6.6	9.3	9.3
ty [Ah]	63	63	63
ange [V]	350~450	350~450	430~550
ver [kW]	3.5	5.0	5.0
ver [kW]	5.0 (for 5 sec.)	7.0 (for 10 sec.)	7.0 (for 10 sec.)
x H x D, mm]	744 x 692 x 206	744 x 907 x 206	744 x 907 x 206
t [kg]	75	97	99.8
tection Rating	IP55		
nication	RS485	RS485	CAN 2.0 B
Cell	UL 1642		
Product	TUV (IEC 62619) / CE / FCC / RCM	UL1973 / TUV (IEC 62619) / CE / FCC / RCM	
	gy [kWh] rgy [kWh] cy [Ah] lange [V] ver [kW] ver [kW] x H x D, mm] t [kg] section Rating nication Cell	Type-R  gy [kWh] 7.0  rgy [kWh] 6.6  rgy [Ah] 63  range [V] 350-450  rer [kW] 3.5  rer [kW] 5.0 (for 5 sec.)  x H x D, mm] 744 x 692 x 206  t [kg] 75  rection Rating IPS  rication RS485  Cell UL 1	Type-R         Type-R           gy [kWh]         7.0         9.8           rgy [kWh]         6.6         9.3           cy [Ah]         63         63           range [V]         350-450         350-450           rer [kW]         3.5         5.0           rer [kW]         5.0 (for 5 sec.)         7.0 (for 10 sec.)           x H x D, mm]         744 x 692 x 206         744 x 907 x 206           t [kg]         75         97           rection Rating         IP55           nication         RS485         RS485           Cell         UL 1642

 $Compatible\ Inverter\ Brands: SMA\ (RESU10H)\ ,\ SolarEdge\ (RESU7H,RESU10H)\ -\ More\ brands\ to\ be\ added$ 

 $<sup>1)</sup> Total\ Energy\ is\ measured\ at\ the\ initial\ stage\ of\ battery\ life\ under\ the\ condition\ as\ follows:\ Temperature\ 25^\circ C$ 

<sup>2)</sup> Usable Energy is based on 95% of Depth of Discharge (Battery cell only)